



UNIVERSAL BLACK BITUMEN PAINT

ALL PURPOSE PAINT FOR THE
PROTECTION OF EXTERNAL
METAL, CONCRETE & BRICKWORK

Marley Waterproofing Universal Black Bitumen Paint is an all purpose bitumen paint which provides waterproof protection for a wide range of substrates including iron, steel, concrete, brickwork, fibre cement and zinc.

Directions for Use

Surface Preparation: All surfaces must be clean, dry and free from grease, oil, dirt and loose material. Destroy any moss or lichen growth using Marley Waterproofing Long Lasting Moss Killer. Marley Waterproofing Universal Black Bitumen Paint can be applied over previous paint systems providing they are adhering well. Loose or blistered paint should be removed as should tar based paint systems. Marley Waterproofing Universal Black Bitumen Paint is not rust inhibitive. Prime iron and steel with suitable rust inhibitive primer, and allow to dry

thoroughly. New galvanised surfaces should be roughened with a wire brush or treated with a proprietary etch primer. Porous substrates (e.g. brickwork, fibre cement etc) should be primed using Marley Waterproofing Quick Drying Roof Primer and allowed to dry. Smooth faced concrete formed with shuttering should not require priming.

Application: Marley Waterproofing Universal Black Bitumen Paint is ready for use and should not be thinned.

Apply a minimum of two coats by brush. Allow each coat to dry (normally 2-4 hours depending on weather conditions) before applying the next. Do not apply when surface temperature is below 5°C.

Coverage: Metal Surfaces: 8 to 10m²/litre per coat.

Concrete, fibre cement etc: 4 to 6m²/litre per coat.

These figures will vary depending on the porosity of the surface.

Cleaning: Brushes and tools can be cleaned with white spirit.

Storage: Containers should be

kept sealed in a cool, dry, well ventilated environment and all practical precautions taken against fire. Partly used containers may be resealed and used again after correct storage. Always store and transport in a secure upright position.

Safe Handling: Keep away from sources of ignition, including pilot lights and sparks - No smoking. In case of fire use foam, dry powder or CO₂ extinguisher, sand or earth. Never use water. Avoid contact with skin by careful working and use of gloves. In case of contact with skin wash immediately with soap or a recognised skin cleanser. Do not use solvents to clean the skin. Use only in well ventilated areas. When using, do not eat, drink or smoke. A safety data sheet is available on request.

Disposal: Do not empty into drains. Remove excess material from tools before cleaning. Some local authorities have special facilities for the disposal of waste liquids. Remove lid and allow residue to dry in a safe place prior to disposal of empty containers.



Sizes Available:

1L - 2.5L - 5L - 25L