



# FLASHING TAPE

GREY SELF ADHESIVE WATERPROOF TAPE IDEAL FOR REPAIRS TO ROOFS, GUTTERS, PIPES AND FLASHINGS

Marley Waterproofing Flashing Tape is an easy to use, grey self adhesive waterproof tape that forms a versatile and long lasting repair over most building surfaces including brick, metal, concrete, asbestos cement and bitumen.

Marley Waterproofing Flashing Tape is particularly suited to the repair of existing flashings, roofing structures, splits in guttering and drainpipes, roof tiles and corrugated sheeting.

#### Directions for Use

##### Surface Preparation:

All surfaces must be clean, dry and free from grease, oil, dirt and loose material. Destroy any moss or lichen growth using Marley Waterproofing Long Lasting Moss Killer. Porous or powdery surfaces must be primed with a coat of Marley Waterproofing Quick Drying Roof Primer and allowed to dry.

##### Application:

Note: Allow Marley Waterproofing Flashing Tape to acclimatise for 24 hours to room temperature (approx. 20°C) prior to use. Do not use when the exterior or base layer temperature is below 5°C. The adhesive tack can be improved in very cold weather by careful warming of the exposed surface of the adhesive coating with a hot air gun.

Cut off the required length of Marley Waterproofing Flashing Tape and remove the release film backing.

Apply to the prepared surface and press into position so that the Marley Waterproofing Flashing Tape closely follows the underlying contours.

Ensure full contact by smoothing down with a cloth pad, taking care to eliminate air bubbles.

Final rolling down of the edges with a seam roller will ensure a good edge seal.

All overlaps must be a minimum of 25mm and rolled down.



#### Marley Waterproofing's Guide to Successful Waterproofing

**STEP 1** Repair localised cracks, leaks and other damaged areas with Marley Waterproofing Universal Roof Repair

**STEP 2** Prime porous surfaces using Marley Waterproofing Quick Drying Roof Primer

**STEP 3** Use Marley Waterproofing Flashing Tape to provide an effective seal for repairs to difficult detailing areas such as pipes, gutters, outlets and upstands