



ROOF & GUTTER REPAIR SEALANT

MASTIC FOR LOCALISED REPAIRS
OF SPLITS AND CRACKS IN ROOF
FELT AND GUTTERS

Marley Waterproofing Roof & Gutter Repair Sealant is a highly flexible sealing compound which provides a long lasting weather seal for joints in gutters, splits and cracks in roofing sheets, flashings and other similar roofing applications.



Directions for Use

Surface Preparation: All surfaces must be clean, dry and free from grease, oil, dirt and other contaminants which may impair adhesion. Destroy any moss and lichen growth using Marley Waterproofing Long Lasting Moss Killer and remove any loose surface material by brushing etc.

Application: Cut the end seal from the threaded part of the tube and fit the nozzle. Cut the nozzle at an angle to the required size. Fit cartridge to a standard gun. Draw the gun along the joint at a steady speed in order to produce a smooth and evenly filled joint. Use a trowel or filling knife to ensure mastic fills the joint making sure that all air pockets are eliminated. Marley Waterproofing Roof & Gutter Repair Sealant is touch-dry in approximately 3 hours.

Coverage: Depending on application, use approximately 8 linear metres per 310ml cartridge with a joint of around 6mm wide by 6mm deep.

Cleaning: Tools can be cleaned with white spirit.

Storage: Store in cool, dry conditions.

Safe Handling: Keep away from sources of ignition, including pilot lights and sparks. In case of fire use foam, dry powder or CO₂ extinguisher, sand or earth. Never use water. Avoid contact with skin by careful working and use of gloves. In case of contact with skin wash immediately with soap or a recognised skin cleanser. Do not use solvents to clean the skin. Use only in well ventilated areas. When using, do not eat, drink or smoke. A safety data sheet is available on request.

Disposal: Remove excess material from tools before cleaning. Some local authorities have special facilities for the disposal of waste liquids.