



UNIVERSAL ROOF RENOVATOR

WATERPROOF COATING FOR SEAMLESS REPAIRS TO FLAT ROOFS

Marley Waterproofing Universal Roof Renovator is a flexible, bituminous coating containing reinforcing fibres designed for easy application to protect and prolong the life of existing roofing systems.

Directions for Use

Surface Preparation: All surfaces must be clean, dry and free from grease, oil, dirt and loose material. Destroy any moss or lichen growth using Marley Waterproofing Long Lasting Moss Killer and prime the surface being treated with Marley Waterproofing Quick Drying Roof Primer and allow to dry. Metal surfaces, where necessary, should be prepared with a wire brush. Prime iron and steel with suitable rust inhibitive primer, and allow to dry thoroughly. Any blisters and cracks present in the existing roof surface should be repaired using Marley Waterproofing Universal Roof Repair.

Application: Stir Marley Waterproofing Universal Roof Renovator thoroughly and then apply an even coating using a brush at a rate of 2.5m²/litre. Allow product to dry thoroughly (approximately 24 hours) and then apply a second coat at right angles to the first at a rate of 2.5m²/litre. For additional ultraviolet protection, slate flakes or chippings can be immediately sprinkled onto the top coat whilst still wet.

Coverage: 2.5m²/litre/coat.

Cleaning: Brushes and tools can be cleaned with white spirit.

Storage: Containers should be kept sealed in a cool, dry, well ventilated environment and all practical precautions taken against fire. Partly used containers may be resealed and used again after correct storage. Always store and transport in a secure upright position.

Safe Handling: Keep away from sources of ignition, including pilot lights and sparks - No smoking. In case of fire use foam, dry powder or CO₂ extinguisher, sand or earth. Never use water. Avoid contact with skin by careful working and use of gloves. In case of contact with skin wash immediately with soap or a recognised skin cleanser. Do not use solvents to clean the skin. Use only in well ventilated areas. When using, do not eat, drink or smoke. A safety data sheet is available on request.

Disposal: Remove excess material from tools before cleaning. Some local authorities have special facilities for the disposal of waste liquids. Remove lid and allow residue to dry in a safe place prior to disposal of empty container.

Sizes Available:

2.5L - 5L - 25L



Marley Waterproofing, Covert Road, Aylesham Industrial Estate, Kent CT3 3EQ diyinfo@marleywaterproofing.com www.waterproofingdiy.com