



RAPID REPAIR SPRAY

SEAL FOR ROOF COVERINGS, GUTTERS AND DRAINPIPES

Marley Waterproofing Rapid Repair Spray is a spray applied mastic formulated to provide rapid sealing on most surfaces, even when damp. It can be effectively used on roofs, gutters and rainwater downpipes.

Marley Waterproofing Rapid Repair Spray will adhere to most surfaces including bitumen felt, fibre cement, tiles, slates, asphalt, metal, wood and most plastics (not polystyrene).



Directions for Use

Surface Preparation: Ensure area to be repaired is clean, dry and free from grease, oil, dirt and loose materials. Destroy any moss and lichen growth using Marley Waterproofing Long lasting Moss Killer. Lightly abrade smooth surfaces to provide a key. Cracks in roof covering and joints in guttering etc. must be filled with Marley Waterproofing Roof & Gutter Repair Sealant prior to the application of Marley Waterproofing Rapid Repair Spray. Surrounding areas should be protected from overspray by masking off with paper or polythene sheet.

Application: Shake well before use. The ideal spraying temperature is between 15°C and 20°C. Lower temperatures will delay drying. Spray across the repair area from a distance of 5cm to 30cm in several light even coats, applying beyond the area to be sealed. Allow to become touch dry between coats when building up thicker applications. Allow 2 to 3 days for Marley Waterproofing Rapid Repair Spray to fully cure when it is intended to apply one of Marley Waterproofing's quality waterproofing membranes or roof repair products.

Coverage: One 500ml can will cover up to 0.15m² depending on application thickness.

Cleaning: Clean any overspray with white spirit. After use invert container and spray to clear nozzle. NB The spray head can be removed for cleaning with white spirit.

Storage: Containers should be stored away from direct heat and sunlight in a cool, dry, well ventilated environment and all practical precautions taken against fire.

Safe Handling: Keep pressurised container away from direct heat, sunlight and exposure to temperatures exceeding 50°C. Keep away from sources of ignition, including pilot lights and sparks - No smoking. In case of fire use foam, dry powder or CO₂ extinguisher, sand or earth. Never use water. Avoid contact with skin and eyes by careful working and use of gloves and eye protection. In case of contact with skin wash immediately with soap or a recognised skin cleanser. Do not use solvents to clean the skin. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Use only in well ventilated areas. When using, do not eat, drink or smoke. A safety data sheet is available on request

Disposal: Do not empty into drains. Some local authorities have special facilities for the disposal of waste liquids. Pressurised container - do not pierce or burn, even after use.