



QUICK DRYING ROOF PRIMER

TO PREPARE AND STABILISE
SURFACES PRIOR TO
APPLYING ROOF FELT AND
FLASHING TAPES

Marley Waterproofing Quick Drying Roof Primer is a deep penetrating bituminous solution for stabilising dusty and porous surfaces prior to the application of Marley Waterproofing Roofing Systems.

When used in conjunction with Marley Waterproofing High Performance Felt Adhesive, the bond between the roof and the waterproofing material being applied is significantly improved and helps ensure a long term, watertight finish.



Directions for Use

Surface Preparation: All surfaces must be clean, dry and free from grease, oil, dirt and loose material. Destroy any moss or lichen growth using Marley Waterproofing Long Lasting Moss Killer. Metal surfaces, where necessary, should be prepared with a wire brush. Marley Waterproofing Quick Drying Roof Primer is not rust inhibitive. Prime iron and steel with suitable rust inhibitive primer, and allow to dry thoroughly.

Application: Marley Waterproofing Quick Drying Roof Primer is ready for use and should not be thinned. Apply a thin even coating with a brush or roller working well into the surface. Allow the primer to dry thoroughly (approx. 3 hours, dependant on weather conditions and surface porosity). Keep the primed surface dust free prior to application of subsequent waterproofing membranes. Do not apply when surface temperature is below 5°C.

Coverage: Dense Concrete: Approximately 6-8 m²/litre.
Porous Brickwork/Blockwork: Approximately 3-5 m²/litre.
Timber Panels: Approximately 4-6 m²/litre. These figures will vary depending on the porosity of the surface.

Cleaning: Brushes and tools can be cleaned with white spirit.

Storage: Containers should be kept sealed in a cool, dry, well ventilated environment and all practical precautions taken against fire. Partly used containers may be resealed and used again after correct storage. Always store and transport in a secure upright position.

Safe Handling: Keep away from sources of ignition, including pilot lights and sparks - No smoking. In case of fire use foam, dry powder or CO₂ extinguisher, sand or earth. Never use water. Avoid contact with skin by careful working and use of gloves. In case of contact with skin wash immediately with soap or a recognised skin cleanser. Do not use solvents to clean the skin. Use only in well ventilated areas. When using, do not eat, drink or smoke.

A safety data sheet is available on request.

Disposal: Do not empty into drains. Remove excess material from tools before cleaning. Some local authorities have special facilities for the disposal of waste liquids. Remove lid and allow residue to dry in a safe place prior to disposal of empty containers.

Sizes Available:

1L - 2.5L - 5L