



HIGH PERFORMANCE WATERSEAL

**EXCEPTIONAL PROTECTION
AGAINST WATER ABSORPTION
AND FROST DAMAGE ON BRICK,
CONCRETE, RENDER AND
TIMBER - IDEAL FOR MASONRY
AND POROUS SURFACES**

Marley Waterproofing High Performance Waterseal is a breathable, transparent waterproofer for use on vertical exterior surfaces such as brick, concrete, stonework, render and timber.

Marley Waterproofing High Performance Waterseal penetrates deep into the surface, providing exceptional protection against water absorption and frost damage.

Directions for Use

Surface Preparation: Remove all dirt and loose material. Destroy any moss or lichen growth using Marley Waterproofing Long Lasting Moss Killer. If the surface is to be washed down do not use wetting agents or detergents. Surfaces should be allowed to dry thoroughly before applying Marley Waterproofing High Performance Waterseal. Repair any cracks, defective pointing, guttering or flashings to make sure water cannot enter because of such faults. Best results are obtained when the weather has been dry for 3 to 4 days and is likely to remain dry for 5 to 6 hours after treatment.



Application: Apply liberally over the whole area by means of a soft brush, starting at the top and working downwards. One application is normally sufficient to give a completely effective treatment, but on very porous surfaces apply a second coat before the first has dried.

Important Information: New render and mortar should be allowed to weather for two months before application of Marley Waterproofing High Performance Waterseal. It is not effective against water pressure and is not suitable for masonry below ground level. Some open texture concrete blocks may not be suitable for treatment. Marley Waterproofing High Performance Waterseal may alter the colouration of some materials, always carry out a small test on an inconspicuous wall section prior to use. This product must not be thinned or allowed to become contaminated with water. Marley Waterproofing High Performance Waterseal can be overpainted with masonry paint after it has been allowed to weather for at least 30 days.

Coverage 2 – 4m² per litre per coat depending on porosity of substrate.

Cleaning Tools can be cleaned with white spirit. Wipe off any splashes immediately with white spirit.

Storage Containers should be kept sealed in a cool, dry, well ventilated environment and all practical precautions taken against fire. Partly used containers may be resealed and used again after correct storage. Always store and transport in a secure upright position.

Safe Handling

Keep away from sources of ignition, including pilot lights and sparks - No smoking. In case of fire use foam, dry powder or CO₂ extinguisher, sand or earth. Never use water. Avoid contact with skin and eyes by careful working and use of gloves and eye protection. In case of contact with skin wash immediately with soap or a recognised skin cleanser. Do not use solvents to clean the skin. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Use only in well ventilated areas. When using, do not eat, drink or smoke. A safety data sheet is available on request.

Disposal: Do not empty into drains. Some local authorities have special facilities for the disposal of waste liquids.

Sizes Available:

2.5L - 5L